ZODIAC HURRICANE TECHNOLOGIES INC. 7830 VANTAGE WAY

DELTA, BRITISH COLUMBIA CANADA, V4G 1A7 PH. (604) 940-2999 FAX (604) 940-2779



Form No.: QC 3-2-1B (General) Form revision: July 9, 2010 Rev 1.04

FINAL DISTRIBUTION

SALE	S ORDER	Boat order:	<u>X</u>	Addn. option	ns: _	Repair order:	Parts Order:	
Customer PO#:	F7059-100058 – Qt. 59	941	Rev	vision #:	6	ZHT Order #:	1990109	

BOAT ORDER OPTIONS LIST

STANDARD ZHT OPTION PACKAGES:

HULI			CACHES SECTION AND THE SECTION	
1	Z-H-7530005		BASE BOAT, H753 OB TWIN	H753 OB BASIC BOAT - Fiberglass hull and deck (standard color gray), non-skid/self-draining deck, complete with motorwell, positive flotation foam. - Below deck cable routing, hull drain, high capacity deck drain scuppers, SS bow eye, 2 SS transom tie-down eyes, 4 recessed lift points. - Removable 5 chamber inflatable collar, Neoprene/Hypalon coated fabric (Neptune Grey), 2 paddles with storage patches, full-length lifeline on D-ring patches, rub strakes. - Foot pump with hose, collar repair kit, and operator's manual. - Tube attachment inserts. - Bilge blower
1	G-F-7532003	3.2.5-C	HULL BOTTOM FOAM CORE, UPGRADE	Upgrade to foam core type hull panel stiffening for the Hull bottom only (transom, deck, and deck plates NOT included).
1	G-F- 7532003-1	3.2.5-C	DECK AND GIRDER FOAM UPGRADE	
1	GD7530005- HGF		AFT DECK COVER, FOAM CORE	
1	GF7534907		SOLAS FOAM FILL	
1	GG7330191- HGF		H733 FUEL COVER PLATE, FOAM CORE	
1	GG7330591- HGF		733 CONSOLE DECK COVER, FOAM CORE	
1	GH7530005- HG		HULL/DECK	
1	ZZ00189		TRANSOM WEDGE SET	
1	G-G-7532803	11.1	BEACHING SHOE, GRP FULL LENGTH	Full length.
1	Z-H-7330708	13.1-1	BOW POST	
1	Z-H- 7331791-HG	13.7-4	BOW BOX, GRP	6.8 cubic feet, 0.193 cubic meter capacity. Colour Gray
1	G-F-7531003	14.0-2	VINYLESTER RESIN, HULL UPGRADE	Upgrade to a fire retardant, vinylester type resin for the Hull and Deck only (deck plates not included).
1	Z-H-7330905	16.6	BOW EYE, RECESSED	Replaces standard SS U-Bolt style bow eye with low profile SS recessed bow eye that protrudes approximately 1/4 inch proud of keel profile.
1	Z-H-7333791	16.7- 1&7	BILGE PUMP, MANUAL	See TSOW section 13.7 (3)
1	ZH7339008- 1	18.1-1	UPGRADE TO HULL CAVITY VENTING	
CONS	OLE		Elitable Control	



DELTA, BRITISH COLUMBIA CANADA, V4G 1A7 PH. (604) 940-2999 FAX (604) 940-2779



Form No.: QC 3-2-1B (General) Form revision: July 9, 2010 Rev 1.04

FINAL DISTRIBUTION

SALES ORDER Boat order: x Addn. options: Repair order: Parts Order: ____

Custon	mer PO#: <u>F7</u>	059-100058	3 – Qt. 5941 Rev	ision #: 6 ZHT Order #: 1990109
1	ZH7367409- 5	13.1-3, 13.2, 13.3.1	STATIC ICE CONSOLE WITH TEE TOP, TEE TOP EXTENDED 6" TO PROVIDE FOR WRITING AREA AND HEAD CLEARANCE W/ LAPTOP SPACE IN FRONT OF HELM	Complete, non-suspension ICE console, affixed to deck. Includes overhead light with red/white capability and full length gutter system with extended length tee top mods. Includes all installation labour including SW Seating. ALL GREY EXTERIOR. INTERIOR TO BE MATT BLACK (NOT INCLUDING OVERHEAD) w/ black dash plate only. With space adequate for 2 VHF radios on overhead console without protruding in to the headroom of the operators. With large capacity storage box located on stbd side, under the dash w/ locking hatch.
1	INCLUDED ABOVE	13.1-3, 13.2, 13.3.1	SHOCKWAVE SEATING	Includes two (2) G-Force seats w/ horizontal & vertical adjust, armrest w/ no handgrips for coxswain, armrest w/ handgrips for navigator, two lateral bolsters, single jump seat aft and storage mounting box with hatches (lockable). Seat belts for all three seating locations.
2	HH15003		HASPS FOR SEAT BOX	
6	LB10005	13.7.3	Padlocks for 6 hatches	
4	HH15002	13.7.3	Swivel hasps for padlocks	
1	ZH7368309- 1	16.4	HEATED FRONT WINDOW	"SEA CLEAR HEATED WINDOW, 1/2" THICK GLASS, BLACK POWDERCOATED FRAME" SUPPLIER IS DIAMOND SEAGLAZE - REQUIRES 110 AV POWER - COSTING INCLUDES 12V-110AV CONVERTER (XANTREX PROWATT 150). Must include top mounted wiper system. SEE TSOW SECTION 16.4.
2	WS14203	13.1-3, 13.2, 13.3.1	LEXAN SIDE SINDOWS UPGRADE	Includes 3/8" lexan side windows. SEE TSOW SECTION 16.4.
1	ZH7365609	13.3.2	RED CHART LAMP STBD SIDE CONSOLE	
1	Z-H- 6488904-2	13.4	SHOREPOWER CHARGER, 3 BATTERIES, 110/12	30 Amp Shorepower system with 110 VAC - 3 breaker panel, Battery charger for 3 batteries with 110 VAC input, 3 x 12 VDC output. Shore power cordset and galvanic isolator not included (available separately).
1	Z-H- 5903397-2	13.6-a	BLUE STROBE	LOPO LIGHT. To be mounted aft, and above the radar scanner on the T-top.
1	NPN	13.6-е	SEPARATE BREAKER FOR PT/STBD LIGHTS	•
1	ZH7336209- 2 IS	3.7.1	13-CIRCUIT ELECTRICAL SYSTEM	Includes LED navigation lights (separate red and green mounted on frame, T-top or cabin and white 360 light mounted on platform mounted folding light mast, approximately 0.9 m high), bilge pump, and horn.
1	Z-H-20175		ADDITIONAL 10- CIRCUIT ELECTRICAL PANEL	Additional panel with 10 breakers.

ZODIAC HURRICANE TECHNOLOGIES INC. 7830 VANTAGE WAY

DELTA, BRITISH COLUMBIA CANADA, V4G 1A7 PH. (604) 940-2999 FAX (604) 940-2779



Form No.: QC 3-2-1B (General) Form revision: July 9, 2010 Rev 1.04

FINAL DISTRIBUTION

S	ALE	S ORD	ER Boat order:	<u>x</u>	Addn. op	tions:	Repair order:	Parts Order:
ustoi	mer PO#:	F7059-10005	8 – Qt. 5941	Rev	ision#:	6	ZHT Order #:	1990109
1	7-H-	372	RATTERV SVSTEM	2	Triple ba	ttery ele	ctrical system for twin	engine 12VDC boats

Custo	mer PO#: F70)59-100058	8 – Qt. 5941 Rev	ision #: 1990109		
1	Z-H- 7341305-4	3.7.2	BATTERY SYSTEM, 2 ENGINES / 3 BATTERIES	Triple battery electrical system for twin engine 12VDC boats. One dedicated starting bank per engine with paralleling ability plus an additional dedicated house bank. Recommended for larger boats and twin diesel inboards. (Batteries and battery boxes not included)		
3	Z-H-7338198	3.7.2-1	BATTERY, 31-1140CCA- 200RC	Battery, series 31, 1140 cold cranking amps, 200 minutes reserve capacity, Maintenance free. Includes battery box.		
1	PB49518	16.7-4	HIGH WATER BILGE ALARM			
2	Z-H-4408491	13.6.1-A	SPOTLIGHT, HANDHELD	Includes marine style accessory plug. On forward face, and dash (communication) side of console.		
2	Z-H- 5905690-1	13.6.1-B	FLOODLIGHTS, HELLA (PAIR)	Available with frame or t-top only. Install one pair on T-top, facing towards the bow on the front corners. Install one pair on T-top, facing port and starboard towards the rear.		
1	Z-H- 7531408-1	13.1-2, 16.8	COMPLETE SELF RIGHTING SYSTEM (AIR)	Includes complete self righting system (air), rope guard, and personnel recovery line.		
1	Z-H-4401608	17.1-1	FIRE EXTINGUISHER, 2.5LB. ABC DRY	ABC dry Chemical fire extinguisher, USCG approved. Installed in Non-Ferrous fire extinguisher bracket.		
1	Z-H-4519903	17.1-6	RING BUOY, 20 INCH W/INSTALL	20 inch diameter USCG approved ring buoy (orange), installed.		
1	ER89268-CN		Nav display - Ray C 140W	C140W Display		
1	ER92131	17.2-3	4 kw Radome – Raymarine	With new display needs a new digital radome, ER92131		
1	MP89113-2- P	17.2-3	RADAR PLATFORM			
1	Z-H-7336606	17.2-4	GPS/WAAS SENSOR, RAY 125	Raymarine Raystar 125 WAAS/GPS sensor. (Unit is NMEA and Seatalk compatible). For use with Raymarine C and E series Multifunction Displays to add WAAS/GPS functionality.		
1	various	17.2-5	Nav system integration			
1	Z-H-6304806	17.2-6	SOUNDER, RAY DSM300, TH MT	Raymarine DSM300, SeaTalkhs Network HDFI Sounder with E66013 (P319), depth only, plastic, Through-Hull mounted transducer. For use with Raymarine C and E series Multifunction Displays to add Depth Sounder functionality. This unit can also have the transducer externally transom mounted by selecting option "TRANSDUCER, BRKT, 14 DEG," GRP.		
1	Z-H- 6624806-1	17.2-6	TRANSDUCER BRACKET, 14 DEGREE, GRP	HD aluminum bracket, to allow P19, P319, P7, ST300 style, Through-Hull transducers to be mounted on aft face of transom, on GRP boats with a 14 degree transom.		
1	ZH6315909- 1	17.2-7	VHF – Ray 218	Includes hailer speaker. Installed on overhead console (with room for a second unit) without protruding into the headroom of operator's standing ahead of the seating.		
1	ZH4726709	17.2-8	EPIRB – ACR RLB-37	and the same of th		
1	Z-H-7331506	17.2-9	HEADING SENSOR, RAY	Raymarine fluxgate Heading Sensor. For use with Raymarine C and E series Multifunction Displays to add fluxgate compass heading, MARPA, and radar/chartplotter overlay mode		

ZODIAC HURRICANE TECHNOLOGIES INC. 7830 VANTAGE WAY

DELTA, BRITISH COLUMBIA CANADA, V4G 1A7 PH. (604) 940-2999 FAX (604) 940-2779



Form No.: QC 3-2-1B (General) Form revision: July 9, 2010 Rev 1.04

FINAL DISTRIBUTION

SALE	S ORDER	Boat order:	<u>X</u>	Addn. option	ıs:	Repair order:	Parts Order:	_
ustomer PO#	F7059-100058 - Ot 59	041	Rev	vision #·	6	ZHT Order #:	1990109	

				functionality.
				500 1
1	Z-H-5301590	3.9-6, 13.6-F	COMPASS, RITCHIE VOYAGER F82	Ritchie Voyager F-82 magnetic compass. 3 inch, flush mount. Includes compass dimmer switch.
1	JC75309- G2L		LABELS	
1	DP31787-4P		AFT ACCESS PLATE	
1	BP31884		MERC BINNACLE POD	
1	PN30632A- BBL		10 CIRCUIT PANEL	
1	DP1990107		OVERHEAD DASH PLATE	
1	DP1990107-2		MAIN DASH PLATE	
PRO	PULSION			
1	various	7.3-2	OBM RUN IN AND INTIAL SERVICE	
1	ZH6305706-	18.0, 3.6.5, 19.0	RIGGING, TWIN MERCURY VERADO SC	Pre-rigging package includes controls, cables, harnesses, gauge (SmartCraft SC1000 series tachometers and speedometer), and Mercury VERADO steering system. Helm on port side of console, with controls on center. Controls to be Mercury Smartcraft dual console mount black with trim.
1	Z-H-5320490	18.0-1	ENGINE MOUNT, TWIN W/PDI & TRIALS	Includes mounting of twin engines, engine Pre Delivery Inspections, and a minimum one hour sea trial.
1	Z-H-7537605	18.1	FUEL SYSTEM – TWIN TANKS FOR TWIN ENGINES	133 US gallons / 504 liters. Includes fuel fill standpipe(s) with cam-lock cap. See TSOW section 13.7 (4). REGARDLESS OF TP1332, BELOW DECK FUEL TANK COMPARTMENT MUST HAVE BOTH PASSIVE AND POWERED BOW TO STERN VENTILATION SYSTEM INSTALLED WITH CLEARLY LABELLED SWITCH AT THE HELM – SEE TSOW SECTION 18.1.
1	PM10600RH	3.6-4	PROPELLOR – RH	MERC PROP, 3 BLADE ,RH, 19"
1	PM10600LH	3.6-4	PROPELLOR – LH	MERC PROP, 3 BLADE ,LH, 19"
1	NPN	3.7.6	UPGRADE TO SS FUEL FITTINGS	
COL	LAR		TU75311-G2	Includes the following:
1	Z-H-7336895	16.9-1	TUBE, RELIEF VALVES W/CAPS - 5 CHAMBER	Over-pressure relief valves with caps
2	Z-H- 4402790-4	16.9-4	TUBE, STEPTREAD, RUBSTRAKE	Single black rubstrake style steptread. Each steptread consists o 2 pieces rubstrake side by side, approximately 24 inches long. <i>Installed in way of the cockpit access, on each side.</i>
2	Z-H-7382890	16.9-5	TUBE, EXTRA ROW RUBSTRAKE (1)	
1	Z-H- 4407508-1	17.1-11	TUBE, BOAT HOOK, 8' TEL W/STORAGE	8 foot telescoping boat hook with storage/attachment patches.

ZODIAC HURRICANE TECHNOLOGIES INC. 7830 VANTAGE WAY

DELTA, BRITISH COLUMBIA CANADA, V4G 1A7 PH. (604) 940-2999 FAX (604) 940-2779



Form No.: QC 3-2-1B (General) Form revision: July 9, 2010 Rev 1.04

FINAL DISTRIBUTION

SALE	S ORDE	R Boat ord	er: X	Addn. options:	Repair order: _	Parts Order:	
astomor BO#s	E7050 100059	Ot 5041	Day	vision # 6	ZUT Order #:	1000100	

1	Z-H-733LC	16.9-6	TUBE, LACING CUFF UPGRADE	Lifeline installed on full length lacing cuff.
ANC	ILLARY			
1	RN30080	17.1-6	Heaving line	
1	SS89984	17.1-7	Flashlight	
1	SS900190	17.1-8	Flares	Contains EF10004 (3) and EF10005 (1).
1	SS90018	17.1-9	Boarding ladder	
1	SS90015	17.1-10	First aid kit	
1	Z-H-85003	17.1-12	ANCHOR PKG W/INSTALLATION, FORTRESS FX7	Fortress FX7 anchor with shackles, 15 feet of chain, and 150 fee of anchor rode, installed.
300	RN80040	13.1-2	TOW LINE	100 M X 3/4". 300 feet required.
1	ZH85101	17.1-13	Sea anchor w/ line	Drogue sea anchor with 100 feet of 1/2" braided nylon line.
4	RN50512-2	17.1-14	Mooring lines	5/8" x 20'
1	LF00151	17.1-15	Rapiditch Express bag	
1	CUSTOM	5.1	EXTRA TECH MANUAL	
1	Z-H- 73394SW	8.1	SHIPPING PREPARATION	
1	SL753T42PG -0 3	16.5-3	ICE DFO LIFT SLING	Certified
1	MP45509-11	16.5.3	SPREADER BAR	
TEST	TING		昭信英语特殊的 经收益的	
1	Z-H-73300-4	7.4-5, 16.5-3	OVERLOAD HOISTING TEST	150% Overload Test on Davit Fittings, or Lift Point Fittings with sling.
TRA	ILER	Water San	REPORT THE RESIDENCE OF THE PARTY OF THE PAR	
1	See front page		HIGHLINER TRAILER	-galvanized, 8500 lb. net carry capacity, tandem axle welded frame ROLLER style trailer - 3" by 5" tubular steel frame -"Hydrostar" electric over hydraulic disc brakes - one adjustable D-ring tie downs, either side, front of fenders - one pair of rear ratchet strap tie downs - spare tire and wheel, on a vertical mount bracket -bolt on, 2 5/16" ball size coupler - full LED lighting package - full length stand on fenders, and four adjustable carpet bunks - "Fulton" F2 model dual wheel jack, 1600 lb. capacity, swivel - 3200 lb. capacity, two speed winch with strap - NAC (National Asset Code) decal

