

COMPACT MK-2 GR

GRAND RAID

SHORT SHAFT – RIGID FLOOR

P/N Z99999



SIMPLE, STRONG, AND RELIABLE

The Grand Raid name is almost as old as Zodiac Milpro itself and has gone through design and feature evolutions to still be very relevant in today's market.

GR's form the backbone of many small boat fleets and are pretty much unique in its full equipment definition.

They continue to answer the needs of users worldwide.

From October 2009, Zodiac Milpro is proposing the Mark-2 GR Next Generation, with a new bow shape, a reinforced fabric, new valves, a large flow self-bailer, and a long shaft transom adapted to 4-stroke engines...



CAPACITY

. maximum number of persons (ISO6185) :	6	6
. maximum payload (ISO6185) :	750 kg	1653 lb
. floorboard usable area :	1,80 m ²	19,38 ft ²
. buoyancy tube volume :	1,20 m ³	42,38 ft ³

ENGINE POWER

. shaft length :	Short	15"
. recommended power :	25 hp	19 kW
. maximum power :	40 hp	30 kW
. maximum engine weight :	85 kg	187 lb

DIMENSIONS

. overall length :	3,80 m	12' 6"
. inside length :	2,27 m	7' 5"
. overall width :	1,75 m	5' 9"
. inside width :	0,84 m	2' 9"
. weight empty :	82 kg	181 lb
. buoyancy tube diameter :	0,45 m	18"
. folded dimensions :	bag 1	1,30 x 0,68 x 0,35 m ³ 4' 3" x 2' 3" x 1' 1"
	bag 2	1,05 x 0,67 x 0,14 m ³ 3' 5" x 2' 2" x 0' 6"

SAFETY / INFLATION

. airtight compartments on main tube :	3
. inflatable keel :	1
. design category (EC 94/25) :	C
. tube inflation pressure :	240 mbar 3,4 PSI

FABRIC

. main buoyancy tube :	grey, 940 dtx, polyamide, CSM / neoprene
. keel buoyancy tube :	black, 940 dtx, polyamide, CSM / neoprene
. bottom :	black, 940 dtx, polyamide, CSM / neoprene

FLOOR

. anti-skid floorboard (anodized aluminium) :	3
. bow floorboard (marine plywood) :	2
. stringers (anodized aluminium) :	2

VALVES

. inflation valves on main tube :	3
. keel inflation valve :	1

TRANSOM BLACK

. large flow self-bailer with sleeve :	1
. standard self bailer with plug :	1
. aluminium engine mounting plate (single engine) :	1
. transom sacrificial plate (marine plywood) :	1

REINFORCEMENTS

. peripheral rubbing strake, flat profile, black :	1
. upper non-slip reinforcement panels :	2
. large transom ovoid reinforcement (940 dtx) :	2
. rubbing strakes underneath keel :	1
. rubbing strakes underneath tubes :	2+2
. transom stainless steel protection shoe :	1
. anti splash triangles :	2

TOWING

. D rings :	stainless steel with black coating
. bow towing D-rings :	2

HANDLING

. carrying handles (molded PVC) :	4
. bow handle :	1
. exterior lifeline (all around) :	1
. interior small D rings :	4

OTHER EQUIPMENT

. foot pump :	1
. repair kit (including pressure indicator) :	1
. paddles (aluminium shaft, plastic blade) :	2
. boat carrying bag :	2

OPTIONAL EQUIPMENT

. V towing bridle bow	. flexible fuel tank (6 USG - 22,7 L)
. launching wheels aft	. watertight bow bag
. launching wheels bow	. waterproof collar pouch
	. deck runners kit (with black strap)

MK-20 GR