

SRR-530

SEA RIB™ RESPONDERS

Navy grey tube : P/N Z99999

EVOLVED FROM A LONG LINE OF RIB

Zodiac Milpro's SEA RIB™ Responders are built for military use. They are simple, functional, tough, and have been designed to improve maintenance and user's comfort.

Their collar is made with Zodiac Milpro's special intercommunicating valves. It is removable to make maintenance and eventual change easier and faster.

The SRR decks are self draining, and feature a molded bow box and aft motor well to provide convenient storage volumes. These boats come with a large capacity built in fuel tank with a deck access hatch to the fuel connections and gauge.



CAPACITY

. maximum number of persons (ISO6185, Design category C) :	12	12
. maximum payload (engine and fuel deducted) (ISO6185, Design category C) :	1150 kg	4409 lb

DIMENSIONS

. overall length (without engine):	5,30 m	17' 05"
. inside length :	4,02 m	13' 02"
. overall width :	2,20 m	7' 03"
. inside width :	1,20 m	3' 11"
. weight empty (hull, fuel tank, collar) :	340 kg	750 lb
. buoyancy tube diameter :	0,500 m	19,69"
. hull storage dimensions :	4,46 x 1,53 x 0,81 m ³	14' 8" x 5' 0" x 2' 8"

ENGINE POWER

. shaft length :	Large	20"
. recommended power :	70 hp	53 kW
. maximum power :	90 hp	68 kW
. maximum engine weight :	189 kg	417 lb

SAFETY / INFLATION

. airtight compartments on main tube :	5
. tube inflation pressure :	240 mbar 3,4 PSI

BUOYANCY TUBE CONSTRUCTION (SLIDE ON)

. fabric :	navy grey, 1670 dtx, polyester, CSM / neoprene
. removable buoyancy tube, bolt rope assembly :	yes
. intercommunication / inflation valves on tube (delrin) :	4
. all around rubbing strake, flat profile, black :	3
. additional bow rubbing strake horizontal, black :	2

HULL CONSTRUCTION (NAVY GREY)

. glass reinforced plastic :	yes
. deck with all surface reinforcements :	yes
. gel coat:	grey

HULL STORAGE

. underdeck fuel tank cavity :	1
with removable deck plate and access hatch :	
. bow box, molded with deck :	1

HULL TRANSOM

. transom sacrificial plate (plywood) :	1
---	---

HULL DRAINING

. self-bailers, large flow :	2
. hull drain :	1

OPTIONAL EQUIPMENT

. Rapid Access Door (RAD)
. lifting sling
. V towing bridle bow
. V towing bridle aft
. bow post
. tow post
. stand-up console (GRP - 1 pers.)
. jockey seat without fuel tank (1 or 2 pers.)
. jockey seat with fuel tank (1 or 2 pers.)
. bolster (1 pers.)
. jockey seat handle
. foot straps
. roll-bar

BUOYANCY TUBE - HANDLING

. exterior lifeline, laced on 53 mm stainless steel D rings :	1+1
. interior lifeline, laced on 25 mm stainless steel D rings :	1+1

HULL - TOWING AND LIFTING

. transom towing rings, stainless steel U-bolt :	2
. bow lifting rings on hull, stainless steel folding padeye :	2
. transom lifting rings, stainless steel U-bolt :	2
. bow mooring eye, stainless steel U-bolt :	1

HULL - FUEL SYSTEM

. fuel tank (rotomolded polyethylene) :	75 L	20 gal US
. fuel sensor & gauge		1+1
. fuel fill and vent, on bow box		1+1
. fuel shut off valve, 2 ways		1

ACCESSORIES

. repair kit :	1
. foot pump :	1
. telescopic paddles :	2

. watertight bow pouch
. ladder
. dive cylinder support (4 or 6)